

表 継手用カップラーおよびナットの寸法(異径用)(単位: mm)

呼名		カップラー							ナット				注入孔径 (mm)
		中央部		全長 Lc	太径側		細径側		太径側		細径側		
		対辺 距離 Wc1	対角 距離 Wc2		長さ	内径	長さ	内径	長さ	内径	長さ	内径	
					Lc1	d1	Lc2	d2	Ln1	d1	Ln2	d2	
1 サイズ 違い	D19-D22	35.9	38.9	117.5	62.5	21.9	55	18.9	20	21.9	20	18.9	5
	D22-D25	40.8	44.2	132.5	70	25.0	62.5	21.9	20	25.0	20	21.9	5
	D25-D29	45.8	49.6	152.5	82.5	28.2	70	25.0	20	28.2	20	25.0	5
	D29-D32	50.6	54.8	172.5	90	31.4	82.5	28.0	30	31.4	20	28.2	5
	D32-D35	55.1	59.6	192.5	102.5	34.5	90	31.4	30	34.5	30	31.4	5
	D35-D38	60.4	65.4	210	107.5	37.5	102.5	34.5	30	37.5	30	34.5	5
	D38-D41	65.8	71.2	218	110.5	40.5	107.5	37.5	30	40.5	30	37.5	5
D41-D51	81.0	87.7	233.5	123	49.3	110.5	40.5	40	49.3	30	40.5	6	
2 サイズ 違い	D19-D25	40.8	44.2	125	70	25.0	55	18.9	20	25.0	20	18.9	5
	D22-D29	45.8	49.6	145	82.5	28.2	62.5	21.9	20	28.2	20	21.9	6
	D25-D32	50.6	54.8	160	90	31.4	70	25.0	30	31.4	20	25.0	6
	D29-D35	55.1	59.6	185	102.5	34.5	82.5	28.2	30	34.5	20	28.2	6
	D32-D38	60.4	65.4	197.5	107.5	37.5	90	31.4	30	37.5	30	31.4	6
	D35-D41	65.8	71.2	213	110.5	40.5	102.5	34.5	30	40.5	30	34.5	6
D38-D51	81.0	87.7	230.5	123	49.3	107.5	37.5	40	49.3	30	37.5	6	
公差		+1.0	+1.0	+3.0		+0.3		+0.3	+0.5	+0.3	+0.5	+0.3	+0.2
		-0.4	-0.4	-1.0		-0.1		-0.1	-0.5	-0.1	-0.5	-0.1	-0.2

